

Section 2 COMBINATION SILL-THRESHOLDS, the “COMBO SILL”

<p>Standard Sizes: 30", 32", 36", 42", 48", 60", 64", 72" (cut exact).</p>	<p>Special fabrications to ease installation with ordering information are described on page 14:</p>	<p>All Combo Sills can be packaged with any door bottom to create a packaged set.</p>
<p>Other lengths are available. (Extra cost over 73") Drop In Sills are cut to exact length ordered.</p>	<p>Rout for nail-on jambs (3/8" - 1-1/4") Mullion rout (MR) Rout for metal/mortised frame (RMF) Sill trim notch (SN) Nail-on rabbet</p>	<p>Sill Covers and Sill Risers are on page 15.</p>
<p>Center holes are countersunk, 1 per door for routed nail-on sill; or, approximately 1 per 12" for drop-in sill. Sills can be ordered without center holes, if desired.</p>	<p>#10 phillips flathead screws are included, length per industry standard.</p>	<p>Special anchors for concrete are available at extra cost, see page 34.</p>
		<p>End Holes are provided with sills routed for nail-on jambs.</p>

SILL-THRESHOLD SELECTION GUIDE

PRODUCT #	WIDTH	HEIGHT	SLOPE	JAMB WIDTH
542	4⁹/₁₆"	1¹/₈"	6°	4¹/₈ to 5
650	5³/₄"	1¹/₈"	9°	4³/₈ to 5¹/₂
569	5⁵/₈"	1¹/₄"	6°	4³/₈ to 5¹/₂
775	7³/₄"	1¹/₄"	9°	6 to 7¹/₈
520	5⁵/₈"	1³/₈"	5°	4³/₈ to 5¹/₂
522	7³/₄"	1³/₈"	5°	6 to 7¹/₈
585	5¹/₈"	1³/₈"	9°	4 to 4⁷/₈
680	6¹³/₁₆"	1³/₈"	9°	5¹/₂ to 6¹/₂

NOTE: Each profile also available for continuous level floor.